



New Race Inspired Neon Graphics

Super-Moto ABS with Rear Disc Brake

PERFORMANCE EVOLUTION **#RTRevolution**
Presenting the **TVS Apache RTR 160 Limited Edition**

Apache
RTR 160
RACING DNA UNLEASHED

RACE PROVEN PERFORMANCE


RTR OVERSQUARE ENGINE

Powered by RTR Oversquare engine. The system has optimised the engine, so that racers can experience the ultimate performance in any race condition.



SUPER-MOTO ABS*

The Single Channel Super-Moto ABS Unit has been conceived and perfected on the track, the system gives the racer total braking control while providing sharp feedback.



MIG SUSPENSION

The rear monotube inverted gas filled 5 step adjustable shocks with rectangular swing arm, ensures cornering aggression meets agility.



SYNCHRO STIFF CHASSIS

The spine of the racing machine provides stiffness for straight-line performance and flex for aggressive cornering. The setup provides the racer absolute confidence to race on the very edge.



CUTTING-EDGE RACE DESIGN

ABS vehicle image used for illustrative purposes only.

RACE-INSPIRED DIGITAL DISPLAY

Designed with race-inspired carbon fibre cues, the countdown-on-ignition speedometer has a distinct white-backlit display.



BEAST-INSPIRED HEADLAMPS

The LED light guide in the headlamp panel along with the pilot lamps produces an intense, raw, animalistic gaze. The throw from the headlamp provides clear visibility.




ALCANTARA-LIKE RACING SEAT

The seat keeps the rider comfortable over long race distances.



NEW RACE GRAPHICS

The graphics on the race machine draw their inspiration from the RTR's conquests on the track.



TVS Apache RTR 160 SPECIFICATIONS

ENGINE

Type	SI, 4 stroke, Air cooled
Engine capacity	159.7 cm ³
Maximum Power	15.2 BHP @ 8500 rpm
Maximum Torque	13.1 Nm @ 6000 rpm
Fuel supply system	Carburettor: UCAL BS-26
Valve per cylinder	2 valves
Starting	Electric & Kick start
Power to weight Ratio	80.6KW per 1000Kg
Cooling system	Air cooled
Gear box	5 speed gear box
Rear Suspension	Monotube Inverted Gas filled shox (MIG) with spring aid
Frame	Double cradle Synchro STIFF
Front Suspension	Telescopic with Hydraulic Dampers. 105 mm Stroke

FUEL TANK CAPACITY

Full	16 l
------	------

DIMENSION

Height	1105 mm
Length	2085 mm
Width	730 mm
Wheelbase	1300 mm
Ground Clearance	165 mm
Saddle Height	790 mm

ELECTRICAL

Battery	12V, 9Ah MF
Headlamp	35/35 W Halogen HS1 Clear lens with MFR with LED position lamp
Tail lamp	LED

TYRE

Tyre (front)	90/90-17 49P Tubeless
Tyre (rear)	120/70 x 17 Tubeless

BRAKE

Front	270 mm dia Petal Disc
Rear	Drum - 130 mm dia Drum
ABS	Disc - 200 mm dia Petal Disc Single Channel Super-Moto ABS

WEIGHTS

Kerb Weight	Rear Drum version - 138 kg
(With 90% fuel & tool kit)	Rear Disc version - 139 kg

*In applicable models only.



Matte Blue



Black



TVS AUTO BANGLADESH LTD



304, Tejgaon I/A (2nd, 3rd & 4th Floor), Dhaka-1208
Tel: +88-02-9831001-2, Fax: +88-02-8891499

www.tvsabl.com TVS Bangladesh 01919189111, 01919194222